

FITTING INSTRUCTIONS FOR

Exterior Rear Molle Panel

SKU	VEHICLE	COMPATIBILITY
KS1027/28	***Toyota Prado 250, Lexus GX 550***	***Platform Racks***



KS1028 (RHS)



KS1027 (LHS)

Included contents

QTY	COMPONENT	QTY	COMPONENT
1	Exterior Molle Panel (LHS or RHS)	2	SwitchBolt Retainer
1	Upper Mount Bracket (LHS or RHS)	5	M8 Nyloc Nut
2	4.5" Suction Cup	2	M8 x 12 Countersunk Socket Screw
2	Suction Cup Bushing	3	M8 x 20 Button Head Socket Screw
6	Rubber Bumper	6	M8 x 16 x 1.5 Washer
2	SwitchBolt	2	M8 x 24 x 2 Washer

Time 30 minutes / Half a beer

Scan the **QR code** to watch the video installation guide,
or for further information contact KAON on **07 3180 1470** or **info@kaon.com.au**

Things to consider before mounting your Exterior Molle.

When using the Exterior Molle Panels to mount accessories to the rear of your vehicle, there are a few things to consider before installation to ensure best practice, safe use and legal compliance.

1. Roof Rack Loading

The Exterior Molle Panels contribute to the overall weight of your roof rack.

As the Exterior Molles are mounted directly to the roof rack, the Panels themselves and any accessories mounted to them will contribute to the overall weight of the rack. It is therefore important to consider the load rating of your rack and ensure that the combined weight of all accessories and the panels do not exceed it.

2. Exterior Molle Panel Loading

Ensure that you adhere to the weight limit when mounting accessories to the panels.

The maximum load each panel can safely carry is 20kg. Ensure that the mounted accessories do not exceed this limit. We recommend mounting Items heavier than 20kgs directly to the roof rack or inside the vehicle.

3. Mounting Dangerous Goods

We do not recommend mounting dangerous goods such as petrol to the Exterior Molle Panels.

Although you may be able to legally mount fuel or other dangerous goods on the Exterior Molle Panels under your local jurisdiction, we advise against using them for this purpose. Refer to **Page 4** for examples of recommended uses for your Exterior Molles instead.

4. Installing with an Awning in Place

Installing an Exterior Molle with an awning is possible, but requires additional steps.

Prior to installing the Exterior Molle you will need to ensure your awning brackets are clear of the mounting space. You will then need to determine whether there is enough space between the awning and rack/vehicle for you to simply feed through the molle's upper mount bracket to attach the panel, or whether you will need to remove awning entirely. These adjustments will need to be made prior to starting this installation.

5. Checks and Maintenance

We recommend doing regular checks and maintenance on your Exterior Molle Panels.

Best practice when using the Exterior Molle Panels includes regularly checking that the suction cups are still fully engaged, ensuring that any mounted accessories are securely fastened and checking that hardware securing them to the rack is also correctly fastened.


6. Legal Compliance for Vehicle Projections

There are legal requirements regarding vehicle projections that must be considered when mounting to the exterior of your vehicle.

Under the Load Restraint Guide for Light Vehicles (2018) by the Australian National Transport Comission, projections must not exceed 150mm from the outermost part of the vehicle on either side. Additionally, the total width of the vehicle and protrusions must not exceed 2500mm.

If you are located outside of Australia, we recommend contacting your local regulatory body to confirm what the legal requirements are for vehicle projections in your area.


Demonstrated below is how to measure the distance from the outermost point on the vehicle. In this example, any accessories mounted on the exterior molle panels must not exceed beyond the blue line.



Recommended uses for the Exterior Molle Panel.

The Exterior Molle Panel was designed with a mesh configuration to suit a number of common camping and touring accessories. Indicated below are examples of accessories suitable for the panel and where you may want to position them on the panel.

This is intended as a guide only, as the accessories you can mount and their location on the panel are not limited to what is displayed here. We recommend determining the configuration that works best for your set-up and the gear you would like to mount.



MAXTRAX MINI

VAAST TANKS

ROTOPAX CONTAINERS

MOLLE/ PALS MESH

GENERAL ACCESSORIES

Let's get to work.

Assembling the Panels

1. Identify the Upper Bracket and attach to the Exterior Molle Panel using the supplied M8 hardware. Ensure that you sandwich a washer on both sides, under the nyloc nut and bolt.

   To be in the correct orientation, the Upper Bracket must be sitting underneath the Exterior Molle Panel, with the arrow pointing toward where the front of the vehicle when installed.

2. Loosely attach the suction cup to the rear of the Molle Panel at the countersunk mounting holes, using the supplied countersunk bolts. Ensure that the supplied TPU bushing is sandwiched between the panel and suction cup.

3. Ensure that the pump on the rearward suction cup is pointing towards the back of the vehicle, while the front suction cup pump should be directed towards the front of the vehicle.

4. It's easiest to attach any accessories to the Molle Panel before mounting it to the vehicle. We recommend a test fit to determine the best configuration for your setup by loosely attaching accessories to the panel and mocking up its final position on the vehicle.

   Ensure that you can still access the pumps on the suction cups and close the door with the accessories. If you're mounting something that may vibrate, use the supplied rubber bumpers in the spare holes on the panel to create a buffer between the panel and accessory.








Assembling the Panels


5. Once the accessory configuration is confirmed, tighten all the hardware excluding the countersunk bolts attaching the suction cups.



Installation

6. Thoroughly clean the rear windows with glass cleaner.
7. In the outermost slat of your roof rack place two SwitchBolts in position over the rear window.
8. Turn the SwitchBolt in the channel, until it sits securely up against the sides, as pictured.
9. Place the retainer over the SwitchBolt to lock its position in the channel. The retainer must be used in order to secure the bolt's position.
10. Place the assembled Exterior Molle Panel over these bolts.
11. Loosely secure the panel in position by fastening a washer and nyloc nut over each SwitchBolt.







Installation

12. Make sure the panel aligns with the shape of the rear window, and check all clearances. Ensure that the suction cup surfaces are parallel to the glass. Their position relative to the glass can be adjusted using the upper bracket mounting slots. With their position confirmed, torque until secure.


13. Remove the covers on the suction cup and push them against the glass.

14. To secure the cup to the glass, apply slight pressure to the panel and pump the mechanism until the white indicator line is no longer visible. This indicates that there is sufficient vacuum and the cup is secure to the vehicle.

15. Tighten the countersunk bolts in the suction cups.

16. That's it, you're done! If you're mounting another Exterior Molle Panel, repeat these installation steps on the other side of your vehicle.

    We recommend periodically checking the suction cup vacuum indicators as part of your vehicle maintenance.









G8.8 Bolt Torque (Non-Lubricated)					
DIAMETER (mm)	5mm	6mm	8mm	10mm	12mm
NEWTON-METRES (Nm)	6 Nm	10 Nm	15 Nm	22 Nm	35 Nm



Local Knowledge & Assistance

We know half the fun of building your dream 4x4 is getting your hands dirty. But we also know that sometimes, things don't go to plan. If in the pursuit to build the ultimate setup you find yourself off-track, we're here to help you get unstuck.

For further information call 07 3180 1470 or email info@kaon.com.au

Disclaimer: The products sold by KAON should not be modified, and are for use only on the vehicles specifically stated. KAON will not be liable for any damages arising out of the use or misuse of it's products. It is the customers responsibility to ensure the products are safely and properly used and installed. KAON consistently seeks to improve it's products and reserves the right to make changes to any product.